



DRILLMEC
DRILLING TECHNOLOGIES

**HH 102 DRILLING/W.O RIG
SEMITRAILER MOUNTED**

Doc.n: DT-110-11

Rev 00

Page 1 of 14



DRILLMEC
DRILLING TECHNOLOGIES

TECHNICAL DOCUMENTATION FRONT SHEET		Page 1 of 14
<u>DOCUMENT TITLE</u>	HH 102 SEMITRAILER	
<u>PACKAGE DESCRIPTION</u>	HH 102 SEMITRAILER	
<u>DOCUMENT NUMBER</u>	DT-110-11	
<u>FILE IDENTIFICATION</u>	DT-110-11 Rev.0 HH 102 Semitrailer	

00	18/05/2011	Technical proposal	ArM	LaU	FeS
<u>Rev. No.</u>	<u>Date of issue</u>	<u>Reason for issue</u>	<u>Prepared</u>	<u>Checked</u>	<u>Approved</u>



1	BASIC RIG	3
2	MAST	3
2.1	TELESCOPIC MAST	3
2.2	CROWN BLOCK	4
2.3	STAND PIPE AND RIG MANIFOLD	4
3	SUBSTRUCTURE	5
3.1	MOUSE HOLE	5
3.2	AUTOMATIC SLIP	5
4	TRAILER	6
4.1	AIR SYSTEM FOR BRAKE AND SUSPENSION	6
4.2	LEVELLING JACKS / RAISING MAST CONTROL PANEL	7
5	TOP DRIVE	7
5.1	TOP DRIVE DOLLY	7
5.2	DOUBLE HOOK	7
5.3	CIRCULATION SWIVEL	8
6	ENGINE	8
7	HYDRAULIC SYSTEM	9
7.1	HYDRAULIC CIRCUIT	9
8	ROTARY TABLE	10
9	RIG LIGHTING SYSTEM	10
10	DRILLER CONTROL CABIN	10
10.1	CONTROL PANEL	11
10.2	WEIGHT INDICATOR	11
11	STANDARD EQUIPMENT	11
11.1	HYDRAULIC POWER TONG	11
11.2	MODULAR PIPE VERTICAL CONTAINER SYSTEM	11
11.3	SERVICE HOIST JIB	12
11.4	TOOL BOX	13
11.5	PRESSURE BALANCED FEED SYSTEM	13
11.6	HYDRAULIC ELEVATION BOP	13
11.7	TORQUE WRENCH	13
11.8	BIT BREAK-OUT AND CASING BACK-UP	14
11.9	INSIDE BOP VALVE (KELLY COCK)	14
11.10	CASING MAKE-UP DEVICE	14

1 BASIC RIG

DRILLMEC semitrailer mounted high mobility rotary drilling & workover rig **Drillmec HH-102** fully hydraulic operated. These followings are the main characteristics:

<i>Equipment</i>	<i>Characteristic</i>
• Drill pipe stands handling	Range 3 (single)
• Max pull	220,000 lbs (100 metric ton)
• Mast clear height from ground level	87,9 ft (26,8m)
• Drilling floor height from ground level	16 ft (4,8m)
• Top drive torque	26,035 ft*lbs (3530 daNm)
• Top drive stroke	52 ½ ft (16 m)
• Max pull down	44,000 lbs (20 metric ton)
• Max power	600 hp (447.5 kW)
• Weight in transport condition	112,728 lbs (51.18 metric ton)
• Ambient temperature	-20°C / +40°C

2 MAST

(DMC Code: Group 01894210)

2.1 TELESCOPIC MAST

The HH-102 hoisting system is based on telescopic mast fabricated in compliance with API 4F, operating as a hydraulic hoist. Made by high strength steel, welded box type and composed by two independent sections: bottom section is fixed to drill floor on trailer and telescopic section is running up and down.

- Raising and lowering of mast by means of hydraulic jack with built-in safety device.
- Telescopic mast is running up and down by hydraulic jack.
- Ladder and handrails to crown block to facilitate lubrication and maintenance
- Safety belt with line hooked up a clutch attachment, to the crown block, to avoid possible operator's fall
- Auxiliary hydraulic winch c/w a jib crane installed on the side of bottom mast section to handle materials on the rig floor and to lift materials from the ground to the rig floor

<i>EQUIPMENT – TEC DATA</i>		<i>Qty</i>
• Max pull	220,000 lb (100 metric ton)	---
• Distance between mast and well center	24 in – (0,61 m)	
• Hydraulic jacks for raising and lowering of mast		2
• Hydraulic jack for mast telescopic		1
• Pull down	20000 kg	
• Max casing Handling	RANGE 3	
Max load auxiliary jib crane		
• Max load on center well	6000kg	
• Max load on mouse hole	4000 kg	
• Max load inside container limit	2000 kg	

2.2 CROWN BLOCK

(DMC Code: Group 01893232)

Crown block is fixed to mast telescopic section complete with

<i>EQUIPMENT – TEC DATA</i>		<i>Qty</i>
Sheaves of crown block		4
• Diameter	30" – (760 mm)	
• Grooves	34 mm	

2.3 STAND PIPE AND RIG MANIFOLD

(DMC Code: Group 01894213- 01894233)

One (1) stand pipe manifold DRILLMEC

The stand pipe will be complete with gooseneck c/w API connection.

The standpipe manifold is fixed on control cabin frame

<i>EQUIPMENT – TEC DATA</i>		<i>Qty</i>
Stand pipe		1
• Pipe diameter	4" OD	---
• Working pressure	5000 psi	---
Rig manifold		
• Union assy	4" FIG. 1002	2
• Gate valve	4" – 5000 psi W.P.	1
• Gate valve	2" – 5000 psi W.P.	4
• Union assy	2" FIG. 1502	4
• Connection for traducer	2" hammer union 5000 psi W.P.	4
• Connection mud pressure gauge	Flanged	2
• Pressure gauge	0-6000	1
Rotary hose		1
• ID	3 1/2"	---
• Working pressure	5000 psi WP	---
• Total length	48 ft – 15. 24m	---
• Connection	4" FIG. 1002 (male x female)	---
Vibrator hose (above control cabin)		1
• ID	3 1/2"	---
• Working pressure	5000 psi WP	---
• Total length	12 ft – 3. 65 m	---
• Connection	4" FIG. 1002 (male x female)	---



3 SUBSTRUCTURE

(DMC Code: Group 01894217)

One (1) Substructure DRILLMEC made of high-grade steel. The substructure and drill floor are directly connected to rig trailer. Due to its specific design, this type of substructure can be easily set also over large existing cellars and the ample space under the substructure floor facilitates the BOP installation.

The substructure is complete with:

- The lower section of the substructure is equipped with rails and trolley to facilitate the sliding of BOP to the well centerline
- Two stairways from drill floor to trailer
- The rotary table is flush with the working floor
- One ramp for casing
- One set of handrails
- Our supply includes steel skids to be placed below the semitrailer leveling jacks

<i>EQUIPMENT – TEC DATA</i>		<i>Qty</i>
1. Drill floor height	16 ft (4,88m)	
2. Clear height under rotary beams	14 ft (4,316 mm)	
3. Control cabin (height, width, length)	8-1/2ft (2.59m)x 8ft (2.43m) x 14 1/2 ft (4.45m)	1

3.1 MOUSE HOLE

(DMC Code: Group 01893354)

Hydraulic clamp installed in the mouse hole and located underneath the drill floor and centered with the mouse hole. It's furnished complete with steel guide to help the pipes to enter the hydraulic clamp.

Max. pipe size: 12".

3.2 AUTOMATIC SLIP

(DMC Code: Group 01904347)

One (1) Set of automatic slips to hang to fit API master bushing and operated from driller's panel to hang 3 1/2", 4 1/2" and 5" drill pipes, complete of a powerful hydraulically operated cylinder to provide pressure rising and pressure setting of slips.



4 TRAILER

(DMC Code:Group 01894366)

One (01) DRILLMEC semitrailer heavy duty type for off-road operation, with:

- Welded frame made of high-grade steel
- Braking system consisting of a double circuit air operated brake plus one (1) additional manually operated brake
- Pneumatic operated front and rear suspension for perfect leveling
- Lighting and road signs
- Lighting system 12v
- Mast support in over-the-road position.
- Tool box
- Walkways and handrails
- Bumper
- Stairs from ground to semitrailer
- King pin for connection to truck, size: 2" and 3 1/2"
- Front neck for 3-axle wheel factor

<i>EQUIPMENT – TEC DATA</i>		<i>Qty</i>
For Semitrailer overall dimensions see attached drawing	S000 5050	
Axles semitrailer		3
Tires singles	525/65 x R20. 5	6+1spare
King pin	3 1/2" (changeable)	1
Hydraulic leveling jacks with mechanical safety locking		4
Hydraulic jack for maintenance on wheel		1

4.1 AIR SYSTEM FOR BRAKE AND SUSPENSION

This air system must connected to truck. This air circuit is utilized for:

- Air brake system
- Leveling shock absorber
- Automatic brake when disconnect truck
- Double level to active and unprime automatic brake

<i>EQUIPMENT – TEC DATA</i>		<i>Qty</i>
1. Tank for air brake	26.4 gal (100 l)	1
2. Tank for air shock absorber	26.4 gal (100 l)	1



4.2 LEVELLING JACKS / RAISING MAST CONTROL PANEL

(DMC Code: Group 01893134)

One control panel for leveling semitrailer and raising mast is mounted in the back of the trailer near tires, complete with:

<i>EQUIPMENT – TEC DATA</i>		<i>Qty</i>
1. Levers commutation (drilling/ installation)		1
2. Levers for leveling jacks (stabilizers)		4
3. Levers for raising mast		1
4. Levers for telescopic mast		1
5. Oil pressure gauge		1

5 TOP DRIVE

(DMC Code: TO BE ASSEGNEED)

Top drive driven by 4 top-head hydraulic motors assembled on a special dolly sliding on mast guide.

Top drive has a special patented device that allows the driller from the control cabin to tilt out the complete top drive from well center to mouse hole

The top drive is equipped with an hydraulic brake

<i>EQUIPMENT – TEC DATA</i>	
• I.D. full opening:	3"
• Variable speed	0 to 154 rpm
• Torque range	0 to 26,000 lbft – (with 100% efficiency)
• Stroke	52' 6"
• Max. pull up	220,000 lbs
• Max. pull down	44,000 lbs
• Max. working pressure	5000 psi

5.1 TOP DRIVE DOLLY

(DMC Code: Group 01894310)

Built with high resistance steel and hydraulically operated, allow the tilting of the top drive from center well to mouse hole for pipe handling. Integrated with top drive and assembled on the mast.

5.2 DOUBLE HOOK

(DMC Code: Group 01894290)

One (1) double hook installed on bottom shaft with the following features:

- Hi-tensile forged heat treated steel
- Suitable to use elevator link
- Equipped with special roller bearing
- Equipped with special air system for the counterbalance of double hook and thread soft landing system

<i>EQUIPMENT – TEC DATA</i>		<i>Qty</i>
<ul style="list-style-type: none"> • Static hook load capacity 	100 metric ton (220,000 lbs)	

5.3 CIRCULATION SWIVEL

(DMC Code: Group 01900101)

The main characteristic of the direct circulation swivel are the following:

- Suitable to drill with air, mud, water and foam
- Wash pipe 3” ID x 5000 psi working pressure
- The packing and wash pipe are designed with quick connections to easily execute maintenance operations.
- The system include standpipe and rotary hose connected to power swivel gooseneck. All pipe and hammer union will be welded to be suitable for working pressure of 5000 psi.

6 ENGINE

(DMC Code: 01894381)

One (1) Diesel engine C18 – ACERT ,with hoisting power of 575 hp at 2100 RPM continuous rate, water cooled and equipped with:

- RPM and working hours gages
- Muffler with spark arrests
- Heavy duty radiator
- Blower fan
- Alternator
- Heavy duty air cleaner
- Governor
- Base rails
- Fuel pump
- Instruments panel
- Emergency shut off
- Electric starter
- Air regulator
- Water separator for fuel
- Air compressor

7 HYDRAULIC SYSTEM

(DMC Code: Group 01894223)

Hydraulic power pack realized with a special coupling between engine and hydraulic pumps this system is used to:

- raising mast
- top drive
- leveling jacks
- hydraulic winch
- power tong
- torque wrench

<i>EQUIPMENT – TEC DATA</i>		<i>Qty</i>
1. Hydraulic pumps		4
• Displacement	7.23 cu in/rev (118.8 cm3/rev)	
• Max pressure (continuos)	5000 psi (350 bar)	---
2. Hydraulic pumps		1
• Displacement	89.7 ml/rev	
• Max pressure (continuos)	3045 psi (210 bar)	
• Displacement	58.3 ml/rev	
• Max pressure (continuos)	3480 psi (240 bar)	
• Displacement	26.4 ml/rev	
• Max pressure (continuos)	3480 psi (240 bar)	
3. Hydraulic pumps		1
• Max delivery	3.14 cu in (51.59cm3/rev)	---
• Max pressure (continuos)	3300 psi (230 bar)	---
4. Oil tank total capacity	449 gal (1700 l)	1
• Oil level indicator, dipstick, filler, drain plug, thermometer		---

7.1 HYDRAULIC CIRCUIT

(DMC Code: Group 01893170)

- Hydraulic cylinder for pull up/down inside mast structure connected to special hydraulic block divider specially made according to Drillmec specifications by first class supplier.
- Hydraulic motor series and cylinders complete with all control devices to move all services for complete rig functionality.
- Hydraulic oil heat exchangers suitable for operation at environment temperature of +40°C.
- Hydraulic oil suitable for coldtemperature (Arctic 32)

8 ROTARY TABLE

(DMC Code: 01894240)

Rotary drive (DRILLMEC) : Independent, hydraulic driven rotary table fabricated in compliance with API 7K Spec. complete with removable API master bushing.

<i>EQUIPMENT – TEC DATA</i>		<i>Qty</i>
1. Rotary table		1
• Opening	20 1/2"	
• Max torque	1000 kgm (7233 ft*lb)	
• Max speed	60 rpm	---
• Max Static hook load on table	220000 lbs (100 metric ton)	---
• Hydraulic motor DANFOSS		2

9 RIG LIGHTING SYSTEM

(DMC Code: 01894360)

<i>EQUIPMENT – TEC DATA</i>		<i>Qty</i>
1. Lighting for Drilling floor and substructure		---
• Metal Jodure light (power / V / Hz)	400W – 110 v – 60 Hz	2
2. Lighting for carrier/semitrailer		---
• Metal Jodure light (power / V / Hz)	400W – 110 v – 60 Hz	2
3. Lighting for control cabin		---
• Neon	36W	6
• Metal Jodure light (power / V / Hz)	400W – 110 v – 60 Hz	5
4. Lighting for pipe racks		
• Metal Jodure light (power / V / Hz)	70W – 110 v – 60 Hz	1
5. Emergency Lighting		---

10 DRILLER CONTROL CABIN

(DMC Code: 01894220)

The driller control cabin is fabricated from heavy-duty steel, according to ergonomic high standard level. The cabin is installed on a skid, it is raised to drilling floor by hydraulic jacks. The access platform to drill floor is flush without steps or stairs, and it is designed in order to include:

- rig floor manifold;
- suitable to accept the choke remote control panel (not included in our supply);
- suitable to accept computerized system to allow the controls management and rig operation visualizing (not included in our supply).

10.1 CONTROL PANEL

(DMC Code: Group 01894241)

L-shaped control panel mounted inside driller control cabin with all controls for drilling operation, motors, make-up and break-out automatic sequences, weight indicator, etc.

Visual instruments for: bit weight, top drive torque, top drive rpm, power tong clamp force, power tong torque, pull down, stand pipe pressure, rotary table torque, etc.

10.2 WEIGHT INDICATOR

(DMC Code: Group 40390641)

Make: WAGNER Type: 13-2 FS

Main features:

- 12" quadrant
- N° 6 lines
- Max Pull 108850 kg (239974 lb) with Pressure 99 bar (1408 psi)

Complete with damper assy and damper saddle

11 STANDARD EQUIPMENT

11.1 HYDRAULIC POWER TONG

(DMC Code: Group 01894359)

Operated from driller's panel, to make-up and break-out drill pipe, and drill collars, consisting of:

- Double hydraulic rotating clamps to close drill pipes and collars joints (from 2 3/8" to 8"), max torque: 8,000 kgm (114,000 Lb-ft).
- Set of hydraulic cylinders for removing the power tongs from well center and parking out.
- Vertical hydraulic cylinder to suspend the power tongs at variable position, operated from driller's panel.

11.2 MODULAR PIPE VERTICAL CONTAINER SYSTEM

(DMC Code: Group 01893268)

The Modular vertical racking system made by vertical bin with unique patented configuration designed to contain all the drill pipes and drill collars to be used.

The concept makes transport as well as drilling operations and string extraction from the well very



easy and fast. The system is composed by vertical container.
The total storage depends on the size and length of drill pipes used; replacing empty container with loaded ones, it is possible to reach greater depth. The system is protected by an international patent. The bottom part of the container is designed in order to install and uninstall very quickly the bins, when necessary.

EQUIPMENT – TEC DATA

		<i>Qty</i>
• Vertical pipe bins		11
• Storage capacity for each pipe bin	5” OD DP, 6⁵/₈” T.J. R3	12 lengths
• Total storage capacity	5” OD DP, 6⁵/₈” T.J. R3	132 lengths, approx 5,800 ft

11.2.1 Drill pipes handling system

- a. By means of the jib you take the drill pipe from the vertical container and put it down in the mouse hole. The joints may have a different length from the standard range used, in fact they are suspended at the right height by means of the hydraulic clamp installed in the mouse hole.
- b. Top drive slides out from the well center and is positioning over the mouse hole; is taking the joint and later is lifting and moving it over the well center in order to add it to the drilling string.
- c. The automatic drilling system makes the operator free to handle other pipes while drilling. If he wants, he may move another drill pipe in the mouse hole. This drill pipe is ready to be taken from the power swivel as per item b.

For the tripping out operations you work backwards.

11.3 SERVICE HOIST JIB

(DMC Code: Group 01894239)

Service hydraulic hoist jib installed on fixed part of telescopic mast with following characteristics:

- Possibility to operate on center well for all material as necessary.
- Possibility to lift material out of substructure frame and operate on working floor or in well center.
- Lifting capacity on working floor, mouse hole and Drill collar parking area 6.000 kg.
- Lifting capacity out of working floor at maximum distance from mast on ground level 2.000 kg.
- Jib crane hydraulically moved by a mobile hydraulic control panel.



11.4 TOOL BOX

(DMC Code: Group 40460013)

One (1) large tool box complete with tools (spanners, pliers, screw drivers, lubrication set, grease gun, oil cans, etc...).

11.5 PRESSURE BALANCED FEED SYSTEM

(DMC Code: Group 01893159)

Drilling conditions can change from foot to foot so you need the best balance between max. drilling speed and min. wear on bits and tools. The rig solves this problem with a pressure balanced feed system that senses the amount of down feed at any instant depending on the formation the bit is drilling and adjust feed automatically and instantly.

11.6 HYDRAULIC ELEVATION BOP

(DMC Code:01894230)

Hydraulic jack to raise BOP. Hydraulic jacks are mounted on bottom of substructure, they raise BOP from trolley and they put BOP stack on well centre. System is featured:

<i>EQUIPMENT – TEC DATA</i>		<i>Qty</i>
Hydraulic jack		2

11.7 TORQUE WRENCH

(DMC Code:01894311)

Q.ty One (1) Hydraulic torque wrench to be used during tripping operation to fast make-up and break-out operations for DP tool joint size from 3 1/2" to 7" OD. The hydraulic wrench is mounted underneath the top drive and is composed of:

- Rotating hydraulic top clamp (hydraulically operated by driller cabin);
- lower hydraulic clamp;
- Suspension double hydraulic jack with 790 mm (2ft 7in) stroke.

Main technical data:

Max make-up torque: 4785 kgm (36,200 ftlbs) to 250 bar
Max break-out torque: 7,000 kgm (50,700 lbs-ft) to 250 bar
Hydraulic jacks stroke: 790 mm (2ft 7in)

11.8 BIT BREAK-OUT AND CASING BACK-UP

(DMC Code: Group 01893148)

Special device for bit break-out and casing back-up composed of a manual tong, actuated by an hydraulic cylinder controlled from main control panel, complete with torque indicator and manual torque regulator.

Main technical data:

- Max torque: 65,000 lbs-ft

11.9 INSIDE BOP VALVE (KELLY COCK)

(DMC Code: Group 01903123)

Hydraulically operated from control panel.

Main technical data:

- Max working pressure: 690 bar (10000 psi)

11.10 CASING MAKE-UP DEVICE

(DMC Code:01894229)

Q.ty One (1) Casing make-up device set to handle 13 3/8" + 9 5/8" + 7" casing sizes.

Q.ty One (1) Casing make-up device set to handle 5" + 4 1/2" casing sizes.

The device is located underneath top drive double hook with gripping patented tool, hydraulically operated from main control panel, which allows the casing rotation with adjustable torque, according to API specification. This device is specially designed to allow fluid circulation during casing running in order to avoid block and tackle with drilled hole wall.